



## PLANET 200S MAXIBAG

### EXCLUSIVE FEATURES

- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ PCB PREFILTER
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ MANUAL FILTER SHAKER
- ▶ TANGENTIAL OR METAL INLET
- ▶ DOUBLE STAGE MOTORS AND TURBINE
- ▶ BIG AND BRAKED WHEELS
- ▶ INDUSTRIAL FRAMEWORK WITH AISI 304 WITH DETACHABLE TANK
- ▶ STARSHAPED FILTER, PCB PREFILTER AND ADDITIONAL CARTRIDGE
- ▶ VACUUM RELIEF VALVE AND FILTRATION LEVEL INDICATOR
- ▶ LONGOPAC®
- ▶ SELF DISCHARGE VALVE WITH BEST SEALING
- ▶ QUICK REPLACEMENT AND DETACHABLE SYSTEM
- ▶ PCB PREFILTER AND ADDITIONAL CARTRIDGE

### PLANET 200S MAXIBAG

Code	ASID00389	
TECHNICAL DATA		
Usage	DRY	
Number of phases	single phase	
Voltage	V	220-240
Frequency	Hz	50-60
N. and type of motor	3x2 stages	
Power	W	3600-3800 max
Water lift	mmH <sub>2</sub> O	2795
Airflow	m <sup>3</sup> /h	630
Bag Capacity	m	20
Diameter of inlet	mm	70
Filtering surface	cm <sup>2</sup>	19.500
Sound Pressure Level	dB(A)	76
Dimensions (LxWxH)	mm	660x900x1450
Weight	Kg	65

### STANDARD EQUIPMENT

CODE: FTDP49548  
FILTERING KIT



CODE: MISC00025  
LONGOPAC®



CODE: FTDP40014  
POLYCARBON PREFILTER



### OPTIONAL ACCESSORIES

Basic tool kit Ø50-70 mm	PMDT00444
Anti-Static tool kit Ø50-70 mm	PMDT00426
Hepa cartridge kit 8.340 cm <sup>2</sup>	FTDP00800

## PLANET 300S MAXIBAG

### EXCLUSIVE FEATURES

- ▶ PCB PREFILTER
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ MANUAL FILTER SHAKER
- ▶ TANGENTIAL OR METAL INLET
- ▶ BIG AND BRAKED WHEELS
- ▶ INDUSTRIAL FRAMEWORK WITH AISI 304 WITH DETACHABLE TANK
- ▶ STARSHAPED FILTER, PCB PREFILTER AND ADDITIONAL CARTRIDGE
- ▶ VACUUM RELIEF VALVE AND FILTRATION LEVEL INDICATOR
- ▶ LONG LASTING TURBINE WITH PERFECT PERFORMANCE
- ▶ LONGOPAC®
- ▶ SELF DISCHARGE VALVE WITH BEST SEALING
- ▶ QUICK REPLACEMENT AND DETACHABLE SYSTEM
- ▶ PCB PREFILTER AND ADDITIONAL CARTRIDGE

### PLANET 300S MAXIBAG

Code	ASID00420	
TECHNICAL DATA		
Usage	DRY	
Number of phases	3 phases	
Voltage	V	400
Turbine	1 single stage	
Power	W	3000
Water lift	mmH <sub>2</sub> O	2500
Airflow	m <sup>3</sup> /h	330
Bag Capacity	m	20
Diameter of inlet	mm	70
Filtering surface	cm <sup>2</sup>	19.500
Sound Pressure Level	dB(A)	77
Dimensions (LxWxH)	mm	660x900x1530
Weight	Kg	85

### STANDARD EQUIPMENT

CODE: KTRI04597  
FILTERING KIT



CODE: MISC00025  
LONGOPAC®



CODE: FTDP40014  
POLYCARBON PREFILTER



### OPTIONAL ACCESSORIES

Basic tool kit Ø50-70 mm	PMDT00444
Anti-Static tool kit Ø50-70 mm	PMDT00426
Hepa cartridge kit 8.340 cm <sup>2</sup>	FTDP00800